OCR640e Desktop Full-page Document Imager & eMRTD Reader

Fast, accurate, reliable multi-illumination full-page desktop MRZ, RFID and 1D/2D barcode reader

Description

The OCR640e Desktop is a full-page multi-illumination ePassport reader. It captures ultraviolet and infrared images, as well the full page of a passport in colour.

In a simultaneous single action the reader also decodes the machine readable zone (MRZ) and processes RFID data – including the holder's image – from the chip.

The OCR640e automatically detects when a document with machine readable data has been presented. Additionally, it is able to compensate for out-of-position MRZ data, so that the advanced recognition engine reliably provides highly accurate and very fast document reading capability, allowing large volumes of documents and smart cards to be processed quickly and efficiently.

The unit features blue, amber, green and red LED lights to keep the user informed of status from ready to scan, through to processing and successful scan; or to indicate that there is an issue with the document. The unit can also be programmed to provide audible feedback to confirm a successful read, signal premature removal of a document and flag a variety of data details.

The OCR640e has a compact, robust design and is designed for years of heavy-duty, frontline use.









Applications

- · Border control, Immigration and Law Enforcement
- · Document and Visa Issuance
- Banking and Mobile Network Operators (KYC & AML)
- · Gaming and Liquor stores (Age Verification)
- Tax Refunds and Money Exchange (Data Capture)
- · Hotels, Airport and Car Rental Check-In

Features

- Captures high-resolution images in multiple wavelengths Visible, IR and UV
- Reads MRZ from ICAO 9303 compliant documents including Passports, e-Passports, ID cards and Visas as well as ISO 18013 compliant driving licences
- ISO 14443 contactless RFID reader/writer supports ICAO LDS standards including BAC, PA, AA, EAC and SAC
- Read 1D/2D barcodes from smartphones, tablets and paperbased documents.

	111	2.	14	6.	80
OCR640-N-Desktop	\checkmark	\checkmark	\checkmark		
OCR640-NB-Desktop	\checkmark	\checkmark	\checkmark		\checkmark
OCR640-E-Desktop	\checkmark	\checkmark	\checkmark	\checkmark	
OCR640-EB-Desktop	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark



OmniData Services Group LLC 11010 Neeshaw Dr., Bldg B Houston, TX 77065, USA +281-469-4365 sales@omnidatasys.net

Access IS 18 Suttons Business Park Reading, Berkshire RG6 1AZ, United Kingdom Tel: +44 (0) 118 966 3333 Access (North America) inc Atlanta, Georgia, USA Airport & Airlines: +1-770-645-2771 ID & Security: +1-703-403-6848 Transport & Ticketing: +44 118 966 3333




Example of device capabilities






Hardware dimensions





Shroud options





OCR640e Desktop ePassport and eID card reader specifications

MRZ reading

Standard OCR fonts: OCR-B

Machine readable passports (MRP): 2 lines of 44 characters to ICAO 9303

Machine readable visas (MRV):

2 lines of 44 characters, 2 lines of 36

characters to ICAO 9303

Travel documents: 2 lines of 36 characters, 3 lines of 30 characters

Imaging

Glass Platen: 4mm Toughened Conturan **Active scan area**: 132mm x 88mm

Full-page: JPG, BMP, TIFF, PNG
Illumination sources: visible/white, IR, UV

LED's

Resolution: 400 DPI

Contactless RFID reading (variant)

Interoperability: ICAO DOC 9303, LDS1.7, ISO18013 (Driving Licence), PA, AA, BAC, EAC v1.11 (CA, TA), EAC v2.0x (PACE v2, ICAO SAC, CA v2, TA v2) Operating frequency: 13.56 MHz

Supported documents: ISO 14443 type A & B auto-detecting; secure and high-speed data transmission; Mifare memory card support (Mifare ultralight, 1K, 4K cards)

Application interface: PC/SC compliant

device

Barcode reading (option)

Linear (1D): EAN / UPC, Code 2 of 5, Interleaved 2 of 5, IATA 2 of 5, Code 39, Code 128 *

Code 120

2D: IATA resolution 792, PDF417, Aztec, DataMatrix and QR codes *

* Full list of supported barcodes available upon request

Mechanical

Size: 163W x 147D x 154H mm

Body: Dark grey ABS

Glass: BS EN60068-2-75 & IEC 62262:2002, rated to 6.375J impact

Weight: 850g

Security: Kensington® security slot

Power supply

+24 VDC via DC iack

Communications & host

Communication: USB 2.0 high speed **Host**: Windows 7 & above, Win 32/64 bit; Pentium-4 3GHz and 2GB RAM minimum

Environmental

Temperature: Operating 0 °C to 50 °C

Storage: 0 °C to 60 °C

Humidity: 0 to 95% non-condensing

Approvals:

FCC 47CFR Part 15 Subpart B Class A, EN 55022 Class B, EN 55024, FCC 47CFR Part 15 Subpart C, ETSI EN 302 291, EN 60950-1

Variant

OCR640n Desktop: As OCR640e but without RFID functionality

Option

Barcode Reading: 1D/2D

Slim Shroud: Low profile, open-faced

Ver: 1.8 January 2016



OmniData Services Group LLC 11010 Neeshaw Dr., Bldg B Houston, TX 77065, USA +281-469-4365 sales@omnidatasys.net Access IS 18 Suttons Business Park Reading, Berkshire RG6 1AZ, United Kingdom Tel: +44 (0) 118 966 3333 Access (North America) inc Atlanta, Georgia, USA Airport & Airlines: +1-770-645-2771 ID & Security: +1-703-403-6848 Transport & Ticketing: +44 118 966 3333

