



Fastmark M4 Series

Full 4" Print Width That Offers
Bluetooth and WiFi Simultaneously

Fastmark M4 – Powerful portable printer that can withstand up to 5 ft drops.

The Fastmark M4 is a rugged mobile printer ready to handle a wide variety of applications, from Healthcare to Warehousing, from receipts to barcode labels. Ready for use with PAL Plus, ZPL, Droid APP & SDK, WinCE Quick-link tool & SDK, and iOS SDK.

Standard Features

- PAL Plus and TSPL-EZ (EPL and ZPL emulations)
- Full 4" width media
- USB, Bluetooth, WIFI interfaces, optional RS-232
- 203 dpi printhead resolution
- Print speeds up to 4 ips
- Easy media loading
- Optional vehicle power adapter
- Belt clip and shoulder strap options
- Direct thermal printing on all popular media material
- 2 year warranty



All M4s are ready for loading custom PAL applications



PRINTER SPECIFICATIONS INCLUDE:

| | | | |
|----------------------------|---|-------------------------------|---|
| Printer Model | Fastmark M4 | Interfaces | Standard: USB and Bluetooth Optional: 802.11 b/g/n WiFi |
| Resolution | 203 dpi | Linear Bar Codes | Code 39, Code 93, Code128UCC, Code 128 subsets A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, ITF14 TELPEN, PLANET, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS |
| Command Set | PAL Plus and TSPL-EZ (EPL and ZPL emulations) | 2D Bar Codes | PDF-417, Micro PDF417, Maxicode, Data Matrix, QR Code, Aztec, Code 49, CODABLOCK F mode, GSI Databar |
| Printing Method | Direct Thermal | Windows compatibility | Win CE, NET, Pocket PC, Windows Mobile2002/2003SE, Windows 2000/XP/Vista/Win 7 |
| Print Speed | Up to 4 ips | Battery | Rechargeable 7.2V DC 5800 mAh Li-on battery |
| Max Print Width | 4.09 inches | Standard items | Belt clip, AC adapter, single battery charger, cleaning pen, sample receipt roll, Quick Guide |
| Max Print Length | 90 inches | Options | Shoulder strap, IP54-rated protective case, Spare Battery, 4 bay Battery charger, Vehicle power adapter, linerless kit |
| Media width | 2.0" – 4.4" | Power | Input: AC 100-240V, 50 – 60Hz 12 VDC 1.25 A output |
| Media Core diameter | .5" to 1" | Environment Conditions | Operation: 14 – 122 F, 10 – 90% non-condensing Storage: -40 – 140 F, 10 – 90% non-condensing |
| Label Roll Capacity | 2.65" OD | Warranty | Two years |
| Media Types | Labels, receipt paper, continuous, die-cut, tag, notch, black mark, fan-fold, linerless | Agency Approval | CE Class B, FCC, CB, CCC, TUV, SRRC |
| Sensors | Gap, black mark reflective, head open, peel | | |
| Enclosure | Plastic with rubber over-mold construction 2 buttons (Power and Feed) 6 LED's for battery status Optional LCD model: 4 buttons(Power, Feed, Menu, Info), 2 LED's and 2" LCD display with backlight Clamshell design with Belt clip or shoulder strap | | |
| Physical Dimension | 3.11" (D) x 6.30" (W) x 7.54" (H) Weight 2.4 lbs with battery | | |
| Real time clock | Standard | | |
| Processor | 32-bit RISC CPU | | |
| Memory | 16MB Flash 32MB SDRAM microSD card reader for Flash expansion up to 4 GB | | |

AMTDatasouth

Corporate Headquarters
803 Camarillo Springs Road, Suite D,
Camarillo, California 93012
(805) 388-5799 PH
(805) 484-5282 FX

www.amtdatasouth.com

Charlotte Operation
5033 Sirona Drive, Suite 800
Charlotte, NC 28273
(704) 523-8500 PH
(704) 525-6104 FX

Part No. 120436 rev. A
Specifications are subject to change without notice.
#16488

