

MICROLINE® 300 Turbo Series

OKI®



Optimize your business performance with reliable, low-cost impact printing

Legendary reliability, expanded head gap, and zero-tear capability for dedicated forms printing

The MICROLINE® 300 Turbo Series of SIDM (dot matrix) printers builds on the OKI® heritage of rugged reliability. These 9- and 24-pin printers are engineered to be tough enough for dedicated printing in the most demanding back office, point-of-sale, automation and utility applications.

They deliver fast output, can easily run twice as long as most printers in their class, and are economical enough to put wherever you need data on the spot.

Getting the job done, day in and day out

ML300 Turbo Series printers put the “work” in workstations for financial departments, wholesale or retail sales counters, even for harsh or warehouse or manufacturing environments. Their relentless performance comes from the design of their printhead... light, strong, efficient motor... long-lasting rack-and-pinion drive system... and a protective, impact-resistant chassis.

These printers can accommodate multipart forms and stock that are up to twice as thick as those that fit their nearest competitors, and their printheads deliver a strong punch—providing clear, crisp text even on the last page of a 6-part form.¹

The ML300 Turbo Series’ patented optical sensor accurately positions printheads for precise output, and their auto-tear feature accurately positions your continuous forms for a clean tear right at the perforation—eliminating wasted forms.

Accommodating your growing business

Drive your office productivity further, with the printers that can meet your needs today and in the future. Options include additional tractor kits, cut sheet feeders, and internal or external network connectivity.

MICROLINE 300 Turbo Series printers: all the reliability and high performance you need.

Highlights:

- Built rugged and reliable in the OKI tradition: 10,000-hr. MTBF
- Expanded head gap handles forms up to twice as thick as the competition’s printers
- Zero-tear and auto-park help to eliminate wasted forms
- Print speeds as fast as 435 cps²
- Crisp, clear printing on up to 6-part forms¹
- Co-resident Epson®, IBM® and MICROLINE® emulations
- USB and parallel connectivity standard
- Available with optional serial interface and network connectivity via internal or external Ethernet print server
- ENERGY STAR® compliant
- 1-year limited warranty standard; up to 3 years of coverage with options³
- Live, toll-free technical support 24/7/365³



ML300 Turbo Series printers are available in standard and wide-body configurations.

¹ ML320/321 models; ML390/391 models up to 4 parts.

² ML320/321 models in SuperSpeed Draft mode.

³ Available in the U.S. and Canada only.

MICROLINE® 300 Turbo Series

Specifications

Technology, Speed and Print Characteristics

- Print Method:** Serial Impact Dot Matrix
ML320T/321T – 9-pin (.34 mm diameter)
ML390T/391T – 24-pin (.2 mm diameter)

- Feed Rate:** 5.0 ips

- Print Speed (cps):**

	LQ	NLQ	Utility	HS Draft	SS Draft
ML320T/321T ¹	n/a	75	300	390	435
ML390T/391T ²	87	n/a	260	n/a	n/a

Emulations, Interface and Memory

Emulations:

ML320T/321T – Epson® ESC/P, IBM® PPR®, (DEC®) ANSI® x 3.64³ and OKI MICROLINE

ML390T/391T – Epson LQ ESC/P2, IBM PPR and IBM AGM

- Interface:** Standard – IEEE Parallel; USB;
Optional – RS-232C Serial; Ethernet via OkiLAN® 10/100 Base-T Internal Print Server or OkiLAN 10/100 Base-T External Print Server

- Memory:** Receive Buffer 128K

Compatibility

- Operating Systems:** Windows® 7, Vista® 32/64, XP, 2000

Paper Handling

- Paper Input:** Single/Multi-part, Continuous forms, Cut sheet, Envelopes, Card stock, Labels
- Number of Copies:** Interleaf or Carbonless
ML320T/321T – Original +5 = 6
ML390T/391T – Original +3 = 4
- Thickness:** Rear feed 0.014" (0.36 mm) max.;
Bottom feed 0.017" (0.44 mm)
- Paper Feeding:** Top/Rear/Bottom
- Standard Tractor:** Rear Push with zero-tear and paper park
- Options:** Top-Mount Pull Tractor, Bottom Push Tractor, Cut Sheet Feeder (single bin), Roll Paper Stand (ML320T and ML390T only)

Environmental

- Size (WxDxH):**
ML320T and ML390T – 15.7" x 13.6" x 4.6" (39.9 cm x 35.5 cm x 11.7 cm)
ML321T and ML391T – 21.7" x 13.6" x 4.6" (55.0 cm x 35.5 cm x 11.7 cm)
- Net Weight:**
ML320T – 12.8 lb. (5.8 kg); ML321T – 16.8 lb. (7.6 kg)
ML390T – 12.8 lb. (5.8 kg); ML391T – 17.0 lb. (7.7 kg)
- Acoustic Noise:** Quiet mode 52 dBA
- Power Requirements:**
120V Model: 100 VAC -10% ~ 127 VAC +10%;
230V Model: 220 VAC -10% ~ 240 VAC +10%

Power Consumption (Avg.):

	Printing	Idle	Sleep Mode ²
ML320/321			
HS Draft	36W	5.0W max	2.0W – 4.2W
Utility	37W		
ML390/391			
LQ Courier	40W	5.0W max	2.0W – 4.2W
Utility	35W		

- Operating Temperature:** 41°F to 95°F (5°C to 35°C);
20% to 80% relative humidity

Warranty and Reliability

- MTBF:** 10,000 hours (25% duty cycle, 35% page density)
- Reliability (Monthly Duty Cycle):**
ML320T – 20,000 pages at 25% duty cycle/35% density;
ML321T – 13,000 pages at 25% duty cycle/35% density
ML390T – 18,000 pages at 25% duty cycle/35% density;
ML391T – 12,000 pages at 25% duty cycle/35% density
- Printhead Life:** 200 million characters at 25% duty cycle
- Ribbon Life:** ML320T/321T – 3 million characters;
ML390T/391T – 2 million characters
- Limited Warranty:** 1-Year parts, labor and printhead;
up to 3 years of coverage available with options⁴

¹ All print speeds apply to all pitches (10, 12, 17.1, and 20 cpi).

² All print speeds apply to 10 cpi pitch only.

³ ML300 Turbo/D is compatible with DEC ANSI 3.64 applications.

⁴ Available in U.S. and Canada only.

For more information on OKI® Dot Matrix (SIDM) printers and supplies, including OKIcare® Extended Service Programs: **1.800.OKI.DATA** (800.654.3282)⁴ or visit www.okidata.com/us

All specifications subject to change without notice.

© 2012 Oki Data Americas, Inc. OKI Reg. T.M., M.D., M.R., MICROLINE, OkilAN, OKIcare Reg. T.M., Oki Electric Industry Co., Ltd. Epson Reg. T.M., Seiko Epson Corp. IBM, ProPrinter Reg. T.M., International Business Machines, Inc. Windows Reg. T.M., Microsoft Corp. PostNet Reg. T.M., USPS. ENERGY STAR Reg. T.M., U.S. EPA.

Ordering Information

Description	Part Number	
MICROLINE 320 Turbo – 120V, 50/60 Hz	62411601	
MICROLINE 320 Turbo – 230V, 50/60 Hz	62411602	
MICROLINE 321 Turbo – 120V, 50/60 Hz	62411701	
MICROLINE 321 Turbo – 230V, 50/60 Hz	62411702	
MICROLINE 320 Turbo/n – 120V	62415401	
MICROLINE 321 Turbo/n – 120V	62415501	
MICROLINE 320 Turbo/D ³ – 120V, 50/60 Hz	62412901	
MICROLINE 320 Turbo/D ³ – 230V, 50/60 Hz	62412902	
MICROLINE 321 Turbo/D ³ – 120V, 50/60 Hz	62413001	
MICROLINE 321 Turbo/D ³ – 230V, 50/60 Hz	62413002	
MICROLINE 320 Turbo with Cut Sheet Feeder (Single Bin) – 120V, 50/60 Hz	62411603	
MICROLINE 321 Turbo with Cut Sheet Feeder (Single Bin) – 120V, 50/60 Hz	62411703	
MICROLINE 390 Turbo – 120V, 50/60 Hz	62411901	
MICROLINE 390 Turbo – 230V, 50/60 Hz	62411902	
MICROLINE 391 Turbo – 120V, 50/60 Hz	62412001	
MICROLINE 391 Turbo – 230V, 50/60 Hz	62412002	
MICROLINE 390 Turbo/n – 120V	62415901	
MICROLINE 391 Turbo/n – 120V	62416001	
MICROLINE 390 Turbo with Cut Sheet Feeder (Single Bin) – 120V, 50/60 Hz	62411903	
MICROLINE 391 Turbo with Cut Sheet Feeder (Single Bin) – 120V, 50/60 Hz	62412003	
Options		
Top-Mount Pull Tractor Kit with Acoustic Cover: ML320T/ML390T	70030501	
ML321T/ML391T	70030601	
Bottom Push Tractor Kit:		
ML320T	70030701	
ML321T	70030801	
Cut Sheet Feeder	70030101	
Roll Paper Stand (ML320T/ML390T only)	70023301	
RS-232C Serial Interface	44455101	
OkilAN® 6130 10/100 Base-T Ethernet Internal Print Server	72008701	
OkilAN® 6020e+ 10/100 Base-T Ethernet External Print Server	70036002	
Self-Inking Ribbon Cartridges:		
ML320T/321T	52102001	
ML390T/391T	52104001	
OKIcare® Depot Warranties⁴		
	U.S.	Canada
ML320T/321T		
2-Year Depot Warranty	38000601	38000611
3-Year Depot Warranty	38000602	38000612
Upgrade to Overnight Exchange	38000603	38000613
ML390T/391T		
2-Year Depot Warranty	38001601	38001611
3-Year Depot Warranty	38001602	38001612
Upgrade to Overnight Exchange	38001603	38001613
OKIcare® Overnight Exchange Warranties⁴		
	U.S.	Canada
ML320T/321T		
2-Yr. Overnight Exchange Wrnty.	38000604	38000614
3-Yr. Overnight Exchange Wrnty.	38000605	38000615
ML390T/391T		
2-Yr. Overnight Exchange Wrnty.	38001604	38001614
3-Yr. Overnight Exchange Wrnty.	38001605	38001615



OKI DATA AMERICAS, INC.

USA

2000 BISHOPS GATE BLVD.
MOUNT LAUREL, NJ 08054-4620
TEL: 800.OKI.DATA (800.654.3282)
FAX: 856.222.5320

CANADA

4140B SLADEVIEW CRESCENT
UNITS 7 & 8
MISSISSAUGA, ONTARIO L5L 6A1
TEL: 905.608.5000
FAX: 905.608.5040

LATIN AMERICA

2000 BISHOPS GATE BLVD.
MOUNT LAUREL, NJ 08054-4620
TEL: 856.231.0002
FAX: 856.222.5071

OKI DATA DE MÉXICO, S.A. DE C.V.

MARIANO ESCOBEDO, 748 8º PISO
COL. NUEVA ANZURES C.P. 11590
MÉXICO, D.F.
TEL: 55.5263.8780
FAX: 55.5250.3501

OKI DATA DO BRASIL INFORMÁTICA LTDA.

AV. ALFREDO EGÍDIO DE SOUZA ARANHA, 100
BLOCO C – 4º ANDAR
04726-170 – SÃO PAULO – SP – BRASIL
TEL: 11.3444.3500
FAX: 11.3444.3502

WWW.OKIDATA.COM

Printed in the USA
MS16043-0312

OKI®