



The fast, affordable, compact POS printer with a 2-Year Overnight Exchange warranty¹

PT330/PT331 printers from OKI: ideal where productivity, economy and space are critical.

Responsive, versatile, efficient and fast—with an extremely short time to first print of 1.95 seconds². PT330/PT331 Series printers are ideal for busy, time-critical and customer-focused environments, such as retail and hospitality.

They're also highly adaptable where space is at a premium: not only do they have a small footprint, they can be positioned either horizontally or vertically, even wall-mounted.


Both models have a recess under the case to neatly conceal interface connectors, and the PT331 has its own built-in power supply.

Flexible and versatile POS printing. PT330/PT331 Series printers can handle a variety of media types and sizes, including the industry standard 83mm-OD roll. They're perfect for receipts, coupons and tickets.

Both models deliver up to 220mm/sec print speed³ with up to 203 dpi resolution. They give you a choice of fonts and a variety of barcodes, including 2-dimensional QR codes. In addition, their internal memory can store up 576 KB, so you can add graphics and logos to your output.

Save paper. And money, too. With PT330/PT331 Series printers, you can reduce the amount of paper you use for receipts—and reduce your costs, as well as your carbon footprint. This can be done in two ways:

- By back-feeding the paper after each receipt prints—the top section usually left blank—you can save up to 5.7% of the paper you use.³



- By using the Windows[®] driver that allows you to shrink the vertical print size, you can slash receipt lengths by up to 50% without losing printed data.⁴

With their long list of features and capabilities, PT330/PT331 Series receipt printers are perfect for your business. And they're backed by a 2-Year Advanced Overnight Exchange warranty and 24/7/365 live technical support.⁴

Highlights:

- **Fast print speed: up to 220mm/sec.²**
- **Robust and reliable – withstand extreme environments**
- **PT331 model has a built-in power supply**
- **Auto cutter (partial cut) – enables clean and easy removal of printed receipts**
- **Models with Serial + USB or LAN connectivity**
- **Buzzer alert function – signals completion of print job; ideal in noisy environments**
- **Optional splash-proof cover – adds protection**
- **Optional wall-mount bracket – adds flexibility**



¹ Available in the U.S. and Canada only.

² Published performance results based on laboratory testing. Individual results may vary.

³ On receipts 150mm in length; 3.5% on receipts 250mm in length.

⁴ Available in 203 dpi mode only.

PT330/PT331 Series

Specifications		
Technology	Print Method	Direct Thermal
	Print Speed	Up to 220mm/second ¹
	Print Resolution	Up to 203 dpi (8 dot/mm)
Interface	Standard	Choice of RS232C Serial + Full-speed USB 2.0 or 10 Base-T/100 Base-TX (RJ-45) Ethernet
Compatibility	Operating Systems	Windows® 7, Windows Vista®, Windows XP, Windows Server 2008, Windows Server 2008 R2, Windows Server 2003, Windows 2000, Windows Embedded POSReady 2009, Windows Embedded for Point of Service, OPOS (v1.13), JavaPOS™ (v1.10) for Windows
	Emulation	Epson® ESC/POS®
Font and Graphics	Character Set	ANK, International Character, Enlarged Graphics, Download Character
	Barcodes	1D: UPC-A, UPC-E, JAN13 (EAN), JAN8 (EAN), CODE 39, ITF, CODABAR (NW-7), CODE 93, CODE 128; 2D: QR code, PDF417, DataMatrix
	Graphic/Logo Storage	384KB/192KB
Paper Handling	Media Width/Print Area	58mm: 48mm (384 dots) or 52.5mm (420 dots); 80mm: 64mm (512 dots) or 72mm (576 dots)
	Media Roll Diameter	Up to 83mm diameter max.
	Media Thickness	0.065mm (65µm) to 0.085mm (85µm)
	Cutter	Partial cut
	Paper Loading	Drop-in
	Sensors	Paper near end; Paper end
Environmental	Size (WxDxH)	PT330: 4.72" x 5.66" x 7.24" (120mm x 144mm x 184mm) PT331: 6.49" x 5.66" x 7.24" (165mm x 144mm x 184mm)
	Weight	PT330: 2.64 lb. (1.2kg); PT331: 3.74 lb. (1.7kg)
	Electrical	PT330: 24VDC, +/- 10%; PT331: 100-240VAC, 50/60Hz
	Operating Temperature/Humidity	32°F to 104°F (0°C to 40°C); 10% to 95% RH, without condensation
	Storage Temperature/Humidity	-4°F to 140°F (-20°C to 60°C); 5% to 95% RH, without condensation
Reliability	Printer	60 million lines (MCBF)
	Printhead	100km
	Cutter	1.5 million cuts (Partial cut)
Warranty	Printer	2-Year Advanced Overnight Exchange ³
Options	Accessories	Splash-proof cover; Wall-mount bracket (PT330 only)

Ordering Information	
Description	Part Number
PT330 Black – Serial/USB (120V)	44925613
PT330 Black – LAN (120V)	44925614
PT331 Black – Serial/USB (120V)	44925615
PT331 Black – LAN (120V)	44925616
Options	
Splash-proof cover	44950502
Wall-mount bracket (PT330 only)	44950402

For more information on Label/POS Printers from OKI, contact your OKI representative. Or visit our Web site: www.okidata.com

For a complete list of OKI print media, please go to our Web site: www.okidata.com

¹ Published performance results based on laboratory testing. Individual results may vary.

² javaPOS driver supports RS232C and USB interface.

³ Available in the U.S. and Canada only.

Specifications are subject to change without notice.

© 2012 Oki Data Americas, Inc. OKI Reg. T.M., Oki Electric Industry Co., Ltd. Windows, Vista Reg. T.M., Microsoft Corp. JavaPOS T.M., Sun Microsystems, Inc. Epson, ESC/POS Reg. T.M., Seiko Epson Corp. USB I/F logo T.M., Universal Serial Bus Implementers Forum, Inc.



OKI DATA AMERICAS, INC.

USA
2000 BISHOPS GATE BLVD.
MOUNT LAUREL, NJ 08054-4620
TEL: 800.OKI.DATA (800.654.3282)
FAX: 856.222.5320

CANADA
4140B SLADEVIEW CRESCENT
UNITS 7 & 8
MISSISSAUGA, ONTARIO L5L 6A1
TEL: 905.608.5000
FAX: 905.608.5040

LATIN AMERICA
2000 BISHOPS GATE BLVD.
MOUNT LAUREL, NJ 08054-4620
TEL: 856.231.0002
FAX: 856.222.5071

OKI DATA DE MÉXICO, S.A. DE C.V.
MARIANO ESCOBEDO, 748 8º PISO
COL. NUEVA ANZURES C.P. 11590
MÉXICO, D.F.
TEL: 55.5263.8780
FAX: 55.5250.3501

OKI DATA DO BRASIL INFORMÁTICA LTDA.
AV. ALFREDO EGÍDIO DE SOUZA ARANHA, 100
BLOCO C – 4º ANDAR
04726-170 – SÃO PAULO – SP – BRASIL
TEL: 11.3444.3500
FAX: 11.3444.3502

WWW.OKIDATA.COM

Printed in the USA
MS16053-0512